

AWUKO Qualities

Name	Characteristics	Grain No.					Areas of Applications		
AWUKO-KP12F antistatic	F-paper, very open coated, aluminium oxide, resin bond	P150-P60	✓	✓	✓	✓		✓	✓
AWUKO-KP52F antistatic	F-paper, semi open coated, aluminium oxide, resin bond	P220-P40	✓	✓	✓			✓	✓
AWUKO-KP80E	E-paper, dense coated, aluminium oxide, resin bond	P800-P24	✓	✓	✓	✓	   	✓	✓
AWUKO-KP80E velcro	our AWUKO KP80E with velcro backing	P400-P24		✓	✓	✓	 	✓	✓
AWUKO-KP80E PSA	our AWUKO KP80E in PSA execution	P800-P40		✓		✓	  	✓	✓
AWUKO-KP32C	flexible C-Latex paper, semi open coated, aluminium oxide, resin bond	P400-P60		✓	✓	✓	 	✓	✓
AWUKO-KP32C velcro	our AWUKO KP32C with velcro backing	P180-P100		✓	✓	✓	 	✓	✓
AWUKO-KP43E	E-paper, dense coated, aluminium oxide, hide glue	2000-P100	✓		✓		 		✓
AWUKO-KP20F	F-paper, open coated, aluminium oxide, resin bond	P400-P120	✓		✓				✓
AWUKO-ZP88F inox express	F-paper, dense coated, zircon corundum, resin bond	220-100	✓						✓
AWUKO-KP88F inox express	F-paper, dense coated, aluminium oxide, resin bond	P400-P240	✓						✓
AWUKO-KP63D painter express	D-paper, special wave-form coating, hide glue	P220-P40		✓	✓		 	✓	✓
AWUKO-KP73C	C-paper, semi open coated, aluminium oxide, hide glue	P400-P60		✓	✓		 	✓	✓
AWUKO-KP73A	A-paper, semi open coated, aluminium oxide, hide glue	P1200-P60		✓	✓		 	✓	✓
AWUKO-SP14A	A-paper, special stearate coating, silicon carbide, hide glue	P400-P150		✓	✓	✓	 	✓	✓
AWUKO-SP14A velcro	our AWUKO SP14A with velcro backing	P400-P150		✓	✓	✓	 	✓	✓
AWUKO-SP14A PSA	our AWUKO SP14A in PSA execution	P400-P150		✓		✓	 	✓	✓
AWUKO-SP23B	B-paper, dense coated, silicon carbide, hide glue	P600-P180	✓	✓	✓			✓	✓
AWUKO-SP23E	E-paper, dense coated, silicon carbide, hide glue	P800-P180	✓	✓	✓			✓	✓
AWUKO-SP40E antistatic	E-paper, dense coated, silicon carbide, resin bond	P600-P150	✓		✓	✓	  	✓	✓
AWUKO-SP40F antistatic	F-paper, dense coated, silicon carbide, resin bond	P120-P24	✓	✓	✓	✓	  	✓	✓
AWUKO-SP48G panel express	G-paper, dense coated, silicon carbide, resin bond	P220-P80	✓				 	✓	✓
AWUKO-SR40A	waterproofed A-paper, silicon carbide, resin bond	P1200-P220		✓				✓	
AWUKO-SR40C	waterproofed C-paper, silicon carbide, resin bond	P180-P60		✓				✓	
AWUKO-KT62X	heavy cotton cloth, dense coated, aluminium oxide, resin bond	P220-P16	✓		✓	✓	   	✓	✓
AWUKO-KT82X	X-flex cotton cloth, dense coated, aluminium oxide, resin bond	P120-P16	✓		✓		 	✓	✓
AWUKO-KT62J	medium-soft cotton cloth, dense coated, aluminium oxide, resin bond	P500-P60	✓	✓	✓		 	✓	✓
AWUKO-KT62W	high-flexible cotton cloth, dense coated, aluminium oxide, resin bond	P800-P60	✓	✓	✓		  	✓	✓



Belt



Disk



Manual grinding



Wood



Leather



Floor



Paper



Roll



Maschine grinding



Metal



Lacquer



Glass



Name	Characteristics	Grain No.					Areas of Applications		
AWUKO-KT20M	soft cotton cloth, dense coated, aluminium oxide, resin bond	P400-P40		✓	✓			✓	
AWUKO-ZT62X	heavy cotton cloth, dense coated, zircon corundum, resin bond	120-24	✓		✓				✓
AWUKO-ZU62Y	heavy polyester cloth, dense coated, zircon corundum, resin bond	100-24	✓		✓				✓
AWUKO-KU62Y panel express	extremely heavy polyester cloth, dense coated, aluminium oxide, resin bond	P120-P16	✓						✓
AWUKO-KU62Y	heavy polyester cloth, dense coated, aluminium oxide, resin bond	P80-P24	✓		✓	✓			✓
AWUKO-KU62R	light polyester cloth, dense coated, aluminium oxide, resin bond	P240-P100	✓		✓	✓			✓
AWUKO-KW62X	heavy waterproofed cotton cloth, dense coated, aluminium oxide, resin bond	P600-P320	✓		✓	✓			✓
AWUKO-SU42Y panel express	extremely heavy polyester cloth, dense coated, silicon carbide, resin bond	P120-P36	✓						✓
AWUKO-SU42Y	heavy polyester cloth, dense coated, silicon carbide, resin bond	P150-P12	✓		✓	✓			✓
AWUKO-SU42R	light polyester cloth, dense coated, silicon carbide, resin bond	P240-P100	✓		✓	✓			✓
AWUKO-SW42X	heavy waterproofed cotton cloth, dense coated, silicon carbide, resin bond	P600-P320	✓		✓	✓			✓
AWUKO-ST10X	heavy cotton cloth, open coated, silicon carbide, resin bond	P20, P16, P12			✓	✓			✓
AWUKO-ST42J	medium-soft cotton cloth, dense coated, silicon carbide, resin bond	P320-P120	✓		✓			✓	✓
AWUKO-KN22T	vulcanized fibre, dense coated, aluminium oxide, resin bond	P320-P16				✓			✓
AWUKO-KT80X	dense coated, aluminium oxide, resin bond, special quality for naumkeag caps	P180-P60							✓
AWUKO-OK96L	polishing combination, cotton fabric on sodium kraft paper	-	✓		✓				✓
Sponges hard	foam sponge, 4-side-coated, aluminium oxide	220-36						✓	
Sponges flexible	soft foam sponge, coated on 4 sides, aluminium oxide	180-60						✓	
Mats black	soft, flexible foam material, coated on 2 sides, silicon carbide	180-60						✓	
Mats white	high flexible foam mat, coated on 1-side	180-60						✓	
AWUKO-Fleece A	nylon fibre fleece, aluminium oxide, resin bond	A280-A100		✓	✓	✓		✓	✓
AWUKO-Fleece S	nylon fibre fleece, silicon carbide, resin bond	S1000-S400		✓	✓	✓		✓	✓
AWUKO-Sanding Screen	sanding screen, silicon carbide, resin bond	180-60				✓			✓
AWUKO-Floor Sanding Pads	available in colour: black, green, maroon, brown, red, beige and white (thin: 10mm / thick: 20mm)	-				✓			✓
AWUKO-Graphite Cloth	graphite cloth available in execution 303, GC, 450 and HD	-		✓	✓				✓

